

20 dBm Single Band RF Repeater (1800 MHz)

Model No.		FRD203
Electrical Specification	ns:	
Frequency Range, MHz		1800
Output Power, dBm	Uplink	10 ± 2
	Downlink	20 ± 2
Gain, dB	Uplink	70 ± 2
	Downlink	70 ± 2
Gain Tuning Range (Manual), dB		30 (1 dB step size)
Pass Band Ripple, dB (p-p)		≤ 3
VSWR		≤ 2.0
Noise Figure @ Max Gain, dB		≤ 6
Impedance, Ω		50
Visual Alarm		LED: Power Supply and Synthesizer Lock / Unlock
Power Specifications		
Power Supply, VAC		230V, 50Hz
Power Consumption, Watt (Max)		35
Mechanical Specificat	ions	
Connectors		N(F)
Mounting Type		Wall
Heat Dissipation		Natural Convection
Environmental Specif	ications	
Operating Temperature, °C		-25 to +55
Relative Humidity, %		95
MTBF, hrs		≥ 50,000

©2023 Frog Cellsat <u>www.frogcellsat.com</u> This document is subject to change without notice.

INDIA HEADQUARTERS

Frog Cellsat Limited, B-3, Sector 65, NOIDA - 201301, Uttar Pradesh, India Tel: +91-120-4859650

MANUFACTURING UNIT

Khasra No.142 Kha and Ga, Mohabewala Industrial Area Dehradun-248110, Uttarakhand, India Tel: +91-135-2640366