

ACTIVE POI

Electrical Specifications			
Supported Technologies & Frequency Bands	LTE850		
	GSM / LTE FDD 900		
	GSM / LTE FDD 1800		
	UMTS / LTE FDD 2100		
	LTE2300		
	LTE2600		
RF Ports	Bands	Chain 1 (Chassis 1)	Chain 2 (Chassis 2)
	LTE850	Select any 16 cards	Select any 16 cards
	GSM900		
	LTE900		
	GSM1800		
	LTE1800		
	UMTS2100		
	LTE2100		
	LTE2300		
	LTE2600		
Total RF Ports (per chassis)	16		
RF Input Range (Min / Max), dBm	Min : 25 / Max : 46		
Modular head End	Yes		
Pass Band Ripple, dB	± 3		
Return Loss, dB	> 18		
Impedance, Ω	50		
Mechanical Specifications			
RF Input Connectors	4.3/10 (F)		
RF Output – Ports / Connectors	Four (2 Tx, 2 Rx) / SMA(F)		
Ingress Protection	IP40		
Application	Indoor		
Dimensions, mm (D x W x H) (Single Chassis)	19” Rack Mount (Height - 6 RU) 460 X 484 X 267		
Heat Dissipation	Inbuilt Fan Cooling		
Temperature, deg C	-10 to +55		
M&C	Yes		
MTBF, Hrs	100,000		

INTERNATIONAL SALES

536, Blenheim Centre, Hounslow, London
TW3 1ND, UK. Tel: +44-7787856914

INDIA HEADQUARTERS

D-213, Sector-63, Noida – 201301,
New Delhi NCR, India. Tel: +91-120-4859650